

LMU1

Under Shelf LED Strip



Product Shown With Optional Sensor



Key Features

- Low voltage Class 2 linear LED strip.
- Optimized for under shelf applications.
- Mounted with integrated magnets or screws.
- Optional motion sensor with six minute delay.

Electrical

- 120VAC input.
- Operating temperature: -40°C to +35°C (-40°F to +95°F)

Mounting

- Mounted with integrated magnets or self-tapping screws.
- Integrated caps hide screw heads.

Construction

- Housing is fabricated from aluminum for maximum durability and is designed to optimize thermal management.
- Lens is frosted acrylic for maximum illumination and eliminate glare.

Optics

- Industry-leading LEDs with 3000K, 4000K and 5000K CCT (minimum 80 CRI).

Warranty

- Backed by US LED's Five-Year Warranty.

Project	Date
---------	------

Catalog Number	Type
----------------	------

Product Performance Summary

Lumen Output	Up to 1,200 lumens
Efficacy	Up to 100 LPW
CRI	≥ 80 CRI
Available CCT	3000K, 4000K, & 5000K
Warranty	Five-Year Warranty

Product Overview

The LMU LED strip light is optimized for under shelf applications. Its small form factor make it easy to conceal under shelves while providing sufficient illumination to the target surface. It can be secured to shelves using either integrated magnets or self-tapping screws. For added energy savings, the LMU also comes with available with an optional motion sensor that turns the light off if no motion is detected.

Product Applications

- Under Shelf Light
- Under Cabinet Light
- Display Light
- Task Light
- Retail Light
- Commercial Light

Product Certifications

- UL Listed
- Complies with UL 2108
- RoHS compliant



Ordering Information ¹

Example: LMU-1-12-36-50-80-Y

Example: PWW-1-24-20

Series	Variant	Power	Length	CCT	CRI	Sensor
LMU1						
1	Standard	12	36"	30	80	N
		12W		3000K	80 CRI	No
				40		Y
				4000K		Yes With Six Minute Fixed Delay
				50		
				5000K		

Power Source Ordering Information

Series	Variant	Output Voltage	Output Power
PWW			
1	Standard	24	20
		24V	20W

1. Requires 24 VDC, Class 2 power source (sold separately).
2. Only available without sensor.

LMU1

Under Shelf LED Strip

Performance Data

Length	Dimensions	Weight	Input Voltage	CCT	System Power Level	Delivered Lumens	Efficacy
36"	36" x 0.75" x 0.55"	0.45 lbs. (0.20kg)	120VAC	3000K/4000K/5000K	12W	1,200	100 LPW

Mounting

