

USDS LED Dome Sphere Pendant



Key Features

- An aesthetically pleasing LED architectural pendant that's ideal for new construction or retrofit applications.
- Class 2 (NEC) compliant design - low voltage, limited power.

Electrical

- 120-277VAC input.
- G9 base lamp holder.
- Operating temperature: -30°C to +35°C (-22°F to +95°F).

Mounting

- Luminaire is ready to be suspended.

Construction

- Housing is anodized aluminum construction for exceptional durability.
- Opal glass globe.
- Dimensions: 13.8" (Diameter) x 6"
- Weight: 6.16 lbs.

Optics

- Uses (3) 5W G9 Lamps (not included).

Warranty

- Backed by US LED's Five-Year Warranty.

Project

Date

Catalog Number

Type

Product Overview

The USDS LED Dome Sphere pendant is a distinctive luminaire that's beautifully designed for today's modern style. Ideal for retail, office lobbies, and other contemporary spaces, this pendant provides energy-efficient LED lighting that's eye-catching for the end user.

Product Applications

- Retail Stores
- Shopping Centers
- Office Spaces
- Lobby Areas
- Convenience Stores
- General Commercial

Product Certifications

- ETL Listed
- Complies with UL 1598 and CSA 22.2
- RoHS compliant



Ordering Information

Example: USDS-1-UNVL-A

Series	Variant	Input Voltage	Finish Color
USDS			
1	Standard	UNVL 120-277V	A Anodized Aluminum